

# 10GPlus Cat6<sub>A</sub> Shielded Solid Patchcord

Datasheet: GD061975v11

**Brand-Rex** | a **LEVITON** company


## APPLICATION

The Brand-Rex Augmented Category 6 Zone solid patchcords give the optimum performance when used as part of the Brand-Rex **10GPlus** cabling system. The low profile boots design makes the 10GPlus Zone solid patchcords an excellent choice for higher density blade connectivity.

The **10GPlus** cabling system is comprised of high performance cables & connectivity which not only provide a reliable platform for all of today's network applications, but is also designed to future-proof networks for the emerging, new, higher speed protocols of tomorrow, such as 10GBASE-T. The **10GPlus** system is classified as an Augmented Category 6 and Class EA product set that is fully backward compatible to Cat6 (Class E) and Cat5e (Class D) products.

## FEATURES

- Compliant with Augmented Cat6 & Class EA Standards.
- Shielded U/FTP Cable type
- CPR rated cable, Bca Eca, Dca, and Cca available
- Low profile boots for higher density blade connectivity
- Flexible & Robust construction
- Smaller and lighter cable construction than equivalent conventional patchcords with solid conductors
- Unique design of Wire Management throughout the connector length to assure consistent performance.
- Performance assessed through rigorous quality control in compliance with the demands of industry standards.
- Highest performance and Quality level of any RJ45 available on the market.
- Suitable for Clip-on Retrofit Coloured Boot Markers
- Designed to have a repeatable, controlled and consistent assembly ensuring optimum performance.
- Backwards compatible to Cat6, Cat5e and designed to be Interoperable with AC6 compliant products
- Available in a variety of lengths



## ORDER INFO (examples)

Brand-Rex Part Number	Item Description	Colour	Weight per Item (nom)	Qty per Pack
AC6PCG100-788HBSE	10GPlus 10m Solid Patch Cord, 26AWG, Eca	Violet	500g	1
AC6PCG200-588HBSC	10GPlus 20m Solid Patch Cord, 26AWG, Cca	Green	750g	1
AC6PCG300-488HBSD	10GPlus 30m Solid Patch Cord, 26AWG, Dca	Blue	1kg	1

Note:- E, D, C, B = CPR level; C = Cca (green as standard), E = Eca (Violet as standard), D = Dca (Blue as standard), B=Bca (orange as standard)

Boots are only available in Slate Grey. If boot colouring is required, a retrofit coloured boot clip can be purchased separately (Ref:- MMCPCHB00z, Where, z=>1=Red, 4=Blue, 5=Green, 6=Yell)

## PART NUMBER BREAKDOWN

# AC6PCGxxx-y88HBSz

	<b>Speciality Tag</b> HBS = Solid Z = CPR Rating  C= Cca, E = Eca, D = Dca, B= Bca
	<b>Cord colours</b> 1 <sup>st</sup> No.= Cable 2 <sup>nd</sup> No.= Boot 1 3 <sup>rd</sup> No.= Boot 2 (Note boot colour always 8)
	<b>Colour (STD)</b> 7 = Violet (Eca) 9 = Orange (Bca) 4 = Blue (Dca) 5 = Green (Cca)
	<b>Length (STD)</b> 100 = 10m 200 = 20m Other lengths available on request
	<b>Group</b> AC6 = Cat6A Generic

## MATERIALS

- PC UL94 V0 rated plastics throughout body
- Plated Phosphor Bronze Screen
- Polypropylene Cable Boot

## CABLE FIRE PERFORMANCE

- Fire Safety rating to IEC 60332-1-2
- Acid Gas Emissions to EN 50267-2-3
- Smoke Production EN 50399

## TYPICAL APPLICATIONS

- Wall and Multi User Outlets
- Patch Panel and CPs
- Suitable for connection to servers, blade servers hubs, switches etc

## ENVIRONMENTAL CONDITIONS

- Operating temperature from 0°C to 50°C at 93% relative humidity, non-condensing
- Storage temperature from -20°C to 70°C

## DIMENSIONS

- Nominal cable diameter: Solid 5.6mm
- Length Tolerance (bracketed length): +/- 1%

*“Brand-Rex is **dedicated to designing, developing and manufacturing sustainable high performance structured cabling and speciality cabling solutions**”*

The information contained in this document is valid and correct at the time of issue. Brand-Rex reserves the right to modify details without notice in light of subsequent standard/specification changes and ongoing technical developments.