

Category 6_A U/FTP Zone EuroClass B2_{ca} Cables

Datasheet: GD103725v4


Brand-Rex | a LEVITON company

APPLICATION

Brand-Rex Zone cables exceed the Category 6_A performance standards in a channel of up to 70m in length. They are specified to 500MHz and are suitable for use in all Class E_A structured wiring cable systems. Zone cables have been designed specifically for the challenges in the data centre environment by being smaller and lighter than equivalent conventional cables. The 10GPlus Zone cable supports 10 Gigabit Ethernet, Gigabit Ethernet, Power over Ethernet, voice and broadband video transmissions at frequencies up to 500MHz.

FEATURES AND BENEFITS

- 26 AWG solid annealed copper wire
- 4 twisted pairs individually screened and cabled together – providing EMI immunity
- Available in a range of sheath materials to suit a variety of installation environments, including CPR fire performance ratings E_{ca}, D_{ca}, C_{ca} and B2_{ca} and colour coded for identification.
- Included in the Leviton and Brand-Rex 25 Year System Warranties when used in conjunction with Leviton or Brand-Rex copper connectivity. System warranties available for qualified projects installed by certified contractors.
- Designed and manufactured in a carbon neutral facility in the UK
- Delivered in 100% recycled packaging



STANDARDS

- Designed and constructed to give optimum electrical performance to the following standards:
 - ISO/IEC 11801 Class E_A, IEC 61156-6
 - EN50173-1 and EN 50288-10-2
 - ANSI/TIA 568C.2
- Supports 10GBASE-T
- Meets design requirements for 802.11ac wireless
- Recommended for PoE standards: IEEE 802.3at types 1 & 2 (PoE & PoE+) up to 25.5W at the powered device (PD)

FIRE CLASSIFICATION

CHARACTERISTIC	IEC STANDARD	EN STANDARD	CPR RATING
Reaction to Fire Classification / EuroClass	-	EN 13501-6	B2ca s1a d1 a1
Single Cable Flame Rating	IEC 60332-1-2	EN 60332-1-2	Pass
Smoke Emission	IEC 61034	EN 61034	Pass
Acid Gas Emission	IEC 60754	EN 60754	Pass

Category 6_A U/FTP Zone EuroClass B2_{ca} Cables

Datasheet: GD103725v4

Brand-Rex | a LEVITON company

PRIMARY ELECTRICAL PARAMETERS

CHARACTERISTIC	SPECIFICATION	TYPICAL PERFORMANCE @ 20°C
Conductor Loop Resistance	Max 28.5 Ω / 100m	23Ω/100m (<17Ω/70m)
Conductor Resistance Unbalance	Max 2%	0.2%
Insulation Resistance	>5GΩ.km	>50GΩ.km
Dielectric Strength	2500 Vdc/2secs	Pass

SECONDARY ELECTRICAL PARAMETERS

CHARACTERISTIC	SPECIFICATION	TYPICAL PERFORMANCE @ 20°C
Velocity of Propagation	<534nsec/100m @ 100MHz	413nsec/100m @ 100MHz
Delay Skew	Max 45nsec/100m @ 100MHz	3nsec/100m @ 100MHz
Mean Characteristic Impedance	100Ω +/- 5Ω @ 100MHz	100Ω ± 3Ω @ 100MHz
Coupling Attenuation	Type 1b	77dB
Transfer Impedance	Grade 2	15mΩ/m @ 10MHz

ELECTRICAL PERFORMANCE

Frequency (MHz)		1	4	10	20	100	200	250	500	550
Insertion Loss (dB/100m)	Standard	3.1	5.7	8.9	12.6	28.7	41.4	46.6	67.9	na
	Typical	2.4	4.4	6.8	9.7	22.0	31.7	35.7	52.0	54.8
NEXT (dB)	Standard	na	66.3	60.3	55.8	45.3	40.8	39.3	34.8	na
	Typical	100.0	100.0	100.0	100.0	94.3	88.9	87.1	81.7	81.0
PSNEXT (dB)	Standard	na	63.3	57.3	52.8	42.3	37.8	36.3	31.8	na
	Typical	97.0	97.0	97.0	97.0	91.3	85.9	84.1	78.7	78.0
ELFEXT (dB/100m)	Standard	na	56.0	48.0	42.0	28.0	22.0	20.0	14.0	na
	Typical	90.0	90.0	90.0	84.8	70.8	64.8	62.8	56.8	56.0
PSELFEXT (dB/100m)	Standard	na	53.0	45.0	39.0	25.0	19.0	17.0	11.0	na
	Typical	87.0	87.0	87.0	81.8	67.8	61.8	59.8	53.8	53.0
Return Loss (dB)	Standard	20.0	23.0	25.0	25.0	20.1	18.0	17.3	17.3	na
	Typical	27.0	30.0	30.0	30.0	25.1	23.0	22.3	20.2	19.9
PSANEXT (dB)	Standard	67.0	67.0	67.0	67.0	62.5	58.0	56.5	52.0	na
	Typical	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
PSAACR-F (dB)	Standard	67.0	66.2	58.2	52.2	38.2	32.2	30.2	24.2	na
	Typical	98.1	96.5	94.5	92.2	82.0	73.9	70.6	57.0	54.6

INSTALLATION

Temperature (Installation)	0°C to +50°C	Min Bend Radius (Installation)	8 x Outer Diameter
Temperature (Operation)	-20°C to +75°C	Min Bend Radius (Operation)	4 x Outer Diameter
Max Tensile Load (Installation)	10kg per simplex cable	Field Test NVP Value	0.80
Segregation Class	Class C		

NB: Network designers should use an attenuation factor of 1.5 when designing with these cables

Category 6_A U/FTP Zone EuroClass B2_{ca} Cables

Datasheet: GD103725v4

Brand-Rex | a **LEVITON**
company

PRINT LEGEND

Example print legend:

[Length Mark]m BRAND-REX a LEVITON company AC6-DCZ-B2ca ZONE CABLE Cat 6A U/FTP EN 50399 EuroClass B2ca s1a d1 a1
NVP 0.80 MADE IN UK [ID number] [Week/Year]

STANDARD PACKAGING SPECIFICATIONS - REELS

Brand-Rex Part Number	Packaging Length (m)	Colour	Nominal Cable Diameter (mm)	Nominal Cable Weight (kg/km)	Reel Size Flange Dia x Width (mm)	Gross Weight (kg/Item)	Items Per Pallet
AC6-DCZ-B2ca-500OR	500	Orange†	5.7	34.7	400 x 400 x 312	19.3	18

STANDARD PACKAGING SPECIFICATIONS - BOXES

Brand-Rex Part Number	Colour	Nominal Cable Diameter (mm)	Nominal Cable Weight (kg/km)	Box Size L x W x H (mm)	Gross Weight (kg/Item)	Items Per Pallet
AC6-DCZ-B2ca-Rlx-305OR [§]	Orange†	5.7	34.7	405 x 265 x 405	10.6	27 or 18 ^{††}

§ = 305m box

† Also available in a range of non-standard colours

†† 3 Layer pallet is 27 boxes, 2 layers is 18

*“Brand-Rex is **dedicated to designing, developing and manufacturing**
sustainable **high performance** structured cabling and speciality **cabling solutions**”*

The information contained in this document is valid and correct at the time of issue. Brand-Rex reserves the right to modify details without notice in light of subsequent standard/specification changes and ongoing technical developments.