



INSULATED RESISTANCE WIRES FOR CAR SEAT HEATING

Conductor			Insulation	
Material	Stranding	Nom. Dia. (mm)	Material	Nom. Dia. (mm)
CuNi	7/0.08	0.240	PTFE	0.53
CuNi	7/0.102	0.300	PTFE	0.61
CuNi	7/0.085	0.255	PTFE	0.60
CuNi	7/0.112	0.336	PTFE	0.72
CuNi	7/0.09	0.270	PTFE	0.57
CuNi	7/0.114	0.340	PTFE	0.64
SPAC	7/0.103	0.310	PTFE	0.70
SPAC	7/0.08	0.240	PTFE	0.53
SPAC	19/0.102	0.510	PTFE	0.79
SPAC	11/0.102	0.390	PTFE	0.72
SPAC	13/0.102	0.420	PTFE	0.73
SPAC	7/0.09	0.270	PTFE	0.80
SPAC	19/0.07	0.350	PTFE	0.67
SPAC	51/0.05	0.387	PTFE	0.69
SPAC	72/0.05	0.490	PTFE	0.82
SPAC	19/0.05	0.250	PTFE	0.55

PRODUCT DESCRIPTION:

Brand-Rex offers a comprehensive range of high performance automotive products including car seat heating wires. Built to ensure comfort, they are versatile and mechanically flexible over a wide range of operating temperatures. Primarily for automotive applications, heating conductor wires are produced in customised sizes with a choice of resistive strand formation to meet the highest standards at competitive prices.

PRODUCT CHARACTERISTICS:

Conductor:	Silver plated copper Copper/Nickel alloys or resistance wire
Insulation:	PTFE FEP PFA MFA