



TYPE 1 RSE/STD/024

Conductor CSA	Maximum Cable Diameter	Typical Weight
mm ²	mm	kg/km
0.50	1.68	6
0.75	1.87	9
1.00	1.99	11
1.50	2.35	20
2.50	2.93	30
4.00	3.65	40

PRODUCT DESCRIPTION:

Designed for the connection of either AC or DC circuits in fixed applications inside of vehicles where space is limited.

PRODUCT CHARACTERISTICS:

Conductor:	Tinned annealed copper wire
Insulation:	Dual layer low smoke and zero halogen compound

Technical Data

Voltage Rating:	600V AC/1000V DC
Operating Temperature:	-25 to +85°C
Test Voltage	
@ 50Hz/15 minutes:	4.5kV
Halogen Content:	Zero

Standards

RSE/STD/024 - Part 6

Colour

Standard colours and alternatives are as indicated in the appropriate specification. For further information contact Brand-Rex.

Ordering

Order Part Number:	RSE Type I-CSA-colour (eg. RSEI-0.75sqmm-red)
--------------------	--

The information contained in this document is valid and correct at the time of issue. However, we reserve the right to modify details without notice in the light of subsequent Standard / Specification changes and ongoing technical developments. Diagram colours are used for representation only.