



TYPE 2 RSE/STD/024

Conductor CSA	Maximum Cable Diameter	Typical Weight
mm <sup>2</sup>	mm	kg/km
0.75	3.10	15
1.0	3.50	20
1.5	3.82	30
2.5	4.30	40
4.0	5.12	60
6.0	5.70	80
10	7.20	130
16	8.60	190
25	10.50	300
35	12.10	410
50	14.10	560
70	17.20	800
95	19.60	1010
150	24.30	1600
240	29.20	2520
300	33.30	3130

**PRODUCT DESCRIPTION:**

Designed for the connection of either AC or DC circuits in either moving or fixed applications inside or outside of vehicles.

**PRODUCT CHARACTERISTICS:**

Conductor:	Flexible tinned annealed copper wire
Insulation:	Modified cross-linked compound
Sheath:	Cross-linked low smoke zero halogen compound

**Technical Data**

Voltage Rating:	600V AC/1000V DC
Operating Temperature:	-25 to +85°C
Test Voltage	
@ 50Hz/15 minutes:	4.5kV
Halogen Content:	Zero

**Standards**

RSE/STD/024 - Part 6

**Colour**

Standard colours and alternatives are as indicated in the appropriate specification. For further information contact Brand-Rex.

**Ordering**

Order Part Number:	RSE Type II-CSA-colour (eg. RSEII-2.5sqmm-red)
--------------------	---

The information contained in this document is valid and correct at the time of issue. However, we reserve the right to modify details without notice in the light of subsequent Standard / Specification changes and ongoing technical developments. Diagram colours are used for representation only.

