



TYPE 3 RSE/STD/024

Conductor CSA	Maximum Cable Diameter	Typical Weight
mm ²	mm	kg/km
50	17.0	650
70	18.9	880
95	20.1	1110
150	24.8	1680
185	27.3	2050

PRODUCT DESCRIPTION:

Designed for the connection of either AC or DC circuits in either moving or fixed applications outside of vehicles.

PRODUCT CHARACTERISTICS:

- Conductor: Stranded tinned annealed copper wire
- Insulation: Modified cross-linked compound
- Sheath: Cross-linked low smoke zero halogen compound

Technical Data

- Voltage Rating: 600V AC/1000V DC
- Operating Temperature: -25 to +85°C
- Test Voltage @ 50Hz/15 minutes: 4.5kV
- Halogen Content: Zero

Standards

RSE/STD/024 - Part 6

Colour

Standard colours and alternatives are as indicated in the appropriate specification. For further information contact BICC Brand-Rex.

Ordering

Order Part Number: RSE Type III-CSA-colour (eg. RSEIII-95sqmm-red)

The information contained in this document is valid and correct at the time of issue. However, we reserve the right to modify details without notice in the light of subsequent Standard / Specification changes and ongoing technical developments. Diagram colours are used for representation only.